




GEM™5000

**PORTABLE GAS ANALYZER
INSTRUMENTATION**



The Next Generation of GEM™ Instrument

The GEM™5000 is designed specifically for use on landfills to monitor Landfill Gas (LFG) Collection & Control Systems. The GEM™5000 samples and analyzes the methane, carbon dioxide and oxygen content of landfill gas with options for additional analysis.

- **Six Times More Accurate and Twice as Fast**
- **NEW Annual** recommended factory service
- **Available with GPS and additional gas detection**



Details on back

➤ *Used For*

Landfill Gas Collection & Control Systems
Environmental Compliance
Landfill Gas to Energy
Subsurface Migration Probes

WWW.LANDTECNA.COM



GEM™5000

PORTABLE GAS ANALYZER INSTRUMENTATION



► Features

- ◆ Measures % CH₄, CO₂ and O₂ Volume, static pressure and differential pressure
- ◆ Calculates balance gas, flow (SCFM) and calorific value
- ◆ CO and H₂S (on Plus models only)
- ◆ High Accuracy and Fast Response Time
- ◆ Lighter and More Compact
- ◆ Certified intrinsically safe for landfill use
- ◆ Annual recommended factory service
- ◆ Calibrated to ISO/IEC 17025
- ◆ 3 year warranty with optional service plan

► Key Benefits

- ◆ Designed specifically for use on landfills to monitor landfill gas (LFG) extraction systems, flares, and migration control systems.
- ◆ No need to take more than one instrument to site
- ◆ Can be used for monitoring subsurface migration probes and for measuring gas composition, pressure and flow in gas extraction systems
- ◆ The user is able to set up comments and questions to record information at site and at each sample point
- ◆ Ensures consistent collection of data for better analysis
- ◆ Streamlined user experience reduces operational times

► Applications

- ◆ Landfill Gas Collection & Control Systems
- ◆ Environmental Compliance
- ◆ Landfill Gas to Energy
- ◆ Subsurface Migration Probes

► Technical Specification

Gas Ranges

Gases Measured	CH ₄	By dual wavelength infrared cell with reference channel	
	CO ₂	By dual wavelength infrared cell with reference channel	
	O ₂	By internal electrochemical cell	
	CO	By internal electrochemical cell	
	H ₂ S	By internal electrochemical cell	
Ranges	CH ₄	0-100% (vol)	
	CO ₂	0-100% (vol)	
	O ₂	0-25% (vol)	
	CO	0-2000ppm***	
	H ₂ S	0-500ppm***	
Gas Accuracy*	CH ₄	0-70% ± 0.5% (vol)	70-100% ± 1.5% FS
	CO ₂	0-60% ± 0.5% (vol)	60-100% ± 1.5% FS
	O ₂	0-25% ± 1.0% (vol)	
	CO(H ₂)**	0-2000ppm ± 1.0% FS	
	H ₂ S	0-500ppm ± 2.0% FS	

* Typical accuracy after calibration as recommended in the operations manual.
 **Hydrogen compensated Carbon Monoxide measurement.
 ***Additional ranges available, contact LANDTEC for more information

Other Parameters

	Unit	Resolution	Comments
Energy	BTU/hr	1000 BTU/hr	Calculated from specific parameters
Static Pressure	in. H ₂ O	0.1 in. H ₂ O	Direct Measurement
Differential Pressure	in. H ₂ O	0.0001 in. H ₂ O	Direct Measurement

Important Note: The information in this document is correct at the time of generation. We do, however, reserve the right to change the specification without prior notice as a result of continuing development.

Pump

Flow	Typically 550cc/min
Flow with 80 in. H ₂ O vacuum	Approximately 80cc/min

Environmental Conditions

Operating Temperature Range	14°F – 122°F (-10°C – 50°C)
Operating Pressure	-100 in. H ₂ O, +100 in. H ₂ O (-250mbar, +250mbar)
Relative Humidity	0-95% non condensing
Barometric Pressure	± 14.7 in.Hg (±500mbar) from calibration pressure
Barometric Pressure Accuracy	± 1% typically

Power Supply

Battery Life	Typical use 8 hours from fully charged
Charge Time	Approximately 3 hours from complete discharge

Certification Rating

ATEX	II 2G Ex ib IIA T1 Gb (Ta= -10°C to +50°C)
ISO17025	ISO/IEC17025:2010 Accreditation #66916
CSA	Ex ib IIA T1 (Ta= -10°C to +50°C) (Canada), AEx ib IIA T1 (Ta= -10°C to +50°C) USA

► Associations



► Certifications



► Contacts

LANDTEC North America
 850 South Via Lata, Suite 112
 Colton, CA 92324
 Phone (800) LANDTEC - (909) 783-3636

Western Sales Office
 (800) 821-0496 • Fax (909) 825-0591

Eastern Sales Office
 (800) 390-7745 • Fax (301) 391-6546

LANDTEC South America
 +55 (11) 5181-6591 • Fax +55 (11) 5181-6585
 www.LANDTEC.com.br



Product designs and specifications are subject to change without notice.
 User is responsible for determining suitability of product.
 LANDTEC, GEM and LAPS are registered with the U.S. Patent and Trademark Office.