

# MINK MM 1324/1322 AV

Dry claw vacuum pumps



VACUUM SOLUTIONS



## Efficient

Substantial energy savings compared to conventional vacuum generators, minimized operating costs

## Nearly maintenance-free

Dry and contact-free operation

## Robust

Proven design, more than 200.000 vacuum pumps in operation

Accessories, spare parts and options

- Aqua version
- ATEX version
- Oxygen version
- Gas-tight version
- Light version
- IoT kit
- Light chemical version (only for MM 1322 AV)


# MINK MM 1324/1322 AV

Dry claw vacuum pumps




VACUUM SOLUTIONS

Dimensional drawing



Pumping speed

Air at 70°F. Tolerance: ± 10%



	MINK MM 1324 AV	MINK MM 1322 AV
Nominal pumping speed	112 ACFM	212 ACFM
Ultimate pressure	45 TORR	112.5 TORR
Nominal motor rating	5.6 HP	10.9 HP
Nominal motor speed	1800 RPM	3600 RPM
Noise level (ISO 2151)	74 dB(A)	82 dB(A)
Weight approx.	660 Lbs.	655 Lbs.
Dimensions (L x W x H)	44.1 x 20.4 x 17.7 inches	46.9 x 21.5 x 17.9 inches
Gas inlet / outlet	2" / 1" NPT	2" / 1¼" NPT

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[info@buschusa.com](mailto:info@buschusa.com) or +1 757 463 7800



CONTACT FORM



CALL NOW