



Enviro-Equipment Inc.
10120 Industrial Drive
Pineville NC 28134

Stock#: 806

Status: In stock, Tested

Dimensions: See cut sheet

Description: Dayton 3XK59 20" Exhaust Fan with 1/2HP 1PH 115V/230 XP Motor





Enviro-Equipment Inc.
 10120 Industrial Drive
 Pineville NC 28134

Technical Specs

| | | | |
|------------------------------|----------------------------------|------------------------------|---|
| Item | Panel Exhaust Fan | Motor Enclosure | Hazardous Location Totally Enclosed Air-Over |
| Type | Direct Drive, Hazardous Location | Motor Insulation | Class B |
| Propeller Dia. (In.) | 20 | Max. Ambient Temp. (F) | 104 |
| CFM @ 0.000-In. SP | 4295 | Height (In.) | 24 |
| CFM @ 0.125-In. SP | 4060 | Width (In.) | 24 |
| CFM @ 0.250-In. SP | 3810 | Max. Depth (In.) | 15 3/8 |
| CFM @ 0.375-In. SP | 3460 | Venturi Clearance Dia. (In.) | 22 |
| CFM @ 0.500-In. SP | 2795 | Venturi Depth (In.) | 3 1/2 |
| Sones @ 0.000-In. SP @ 5 Ft. | 24 | Mounting Position | Horizontal or Vertical |
| Voltage | 115/230 | Flange Width (In.) | 1 |
| Hz | 60 | Number of Blades | 4 |
| Phase | 1 | Propeller Material | Fabricated Spark-Resistant Cast Aluminum |
| Full Load Amps | 7.8/3.9 | Frame Material | Steel |
| Watts | 614 | Frame Finish | Gray Baked-On Polyester |
| Motor HP | 1/2 | Agency Compliance | AMCA, UL, CUL |
| Bearing Type | Ball | For Use With | Class I, Group C and D, Class II, Group F and G |
| Motor RPM | 1725 | Aluminum Wall Shutter No. | 4C559 |
| Motor Type | Capacitor-Start | Intake Guard No. | 6D584 |