



**Stock # PR-EEI-1660**

**Used Rotron EN523M72L Regenerative Blower. 208-230/460, 3-Phase, 3HP, Explosion Proof Motor. Stock # 1660**


**PILOT TEST UNIT SPECIFICATIONS**

**Dimensions:** 19.5" x 15" x 16"

**Weight:** 120-Lbs

**Brand:** Ametek Rotron  
**Model:** EN523M72L  
**Max Pressure:** 158" H2O  
**Max Vacuum:** 138" H2O  
**Maximum Flow:** 84 SCFM  
**Inlet/Outlet:** 1.5" FNPT

**Explosion Proof Motor:** Yes  
**Motor:** Baldor  
**HP:** 3  
**Voltage:** 208-230/460  
**Phase:** 3





**Environmental / Chemical Processing Blowers**

**EN 523 & CP 523**

3.0 HP High Pressure Sealed Regenerative w/Explosion-Proof Motor

**ROTRON®**

**FEATURES**

- Manufactured in the USA - ISO 9001 and NAFTA compliant
- Maximum flow: 84 SCFM
- Maximum pressure: 140 IWG
- Maximum vacuum: 135 IWG
- Standard motor: 3.0 HP, explosion-proof
- Cast aluminum blower housing, impeller, cover & manifold; cast iron flanges (threaded); teflon® lip seal
- UL & CSA approved motor with permanently sealed ball bearings for explosive gas atmospheres Class I Group D minimum
- Sealed blower assembly
- Quiet operation within OSHA standards

**MOTOR OPTIONS**


- International voltage & frequency (Hz)
- Chemical duty, high efficiency, inverter duty or industry-specific designs
- Various horsepower for application-specific needs

**BLOWER OPTIONS**

- Corrosion resistant surface treatments & sealing options
- Remote drive (motorless) models
- Slip-on or face flanges for application-specific needs

**ACCESSORIES**

- Flowmeters reading in SCFM
- Filters & moisture separators
- Pressure gauges, vacuum gauges, & relief valves
- Switches - air flow, pressure, vacuum, or temperature
- External mufflers for additional silencing
- Air knives (used on blow-off applications)
- Variable frequency drive package



This document is for informational purposes only and should not be considered as a binding description of the products or their performance in all applications. The performance data on this page depicts typical performance under controlled laboratory conditions. AMETEK is not responsible for blowers driven beyond factory specified speed, temperature, pressure, flow or without proper alignment. Actual performance will vary depending on the operating environment and application. AMETEK products are not designed for and should not be used in medical life support applications. AMETEK reserves the right to revise its products without notification. The above characteristics represent standard products. For product designed to meet specific applications, contact AMETEK Technical & Industrial Products Sales department.



**Enviro-Equipment, Inc.**  
**Remediation Division**




**Environmental / Chemical Processing Blowers**

**EN 523 & CP 523**

3.0 HP High Pressure Sealed Regenerative w/Explosion-Proof Motor

**ROTRON®**



IN  
MM

- NOTES  
 1. TERMINAL BOX CONNECTOR HOLE 3/4" NPT FEMALE THREAD.  
 2. DRAWING NOT TO SCALE, CONTACT FACTORY FOR SCALE CAD DRAWING.  
 3. CONTACT FACTORY FOR BLOWER MODEL LENGTHS NOT SHOWN.

Specification	Units	Part/Model Number			
		EN523M5L 038223	EN523M72L 038184	CP523FU6LR TBD	CP523FU72LR 038968
Motor Enclosure - Shaft Mt.	-	Explosion-proof-CS	Explosion-proof-CS	CHEM XP-88	CHEM XP-88
Horsepower	-	3	3	3	3
Phase - Frequency Voltage	-	Single-60 Hz	Three-60 Hz	Single-60 Hz	Three-60 Hz
Motor Nameplate Amps	AC	280	230/460	280	230/460
Max. Blower Amps	Amps (A)	15.5-14.5	7.4/3.7	15.5-14.5	7.4/3.7
Locked Rotor Amps	Amps (A)	18.1-18.7	84	18.1-18.7	84
Service Factor	Amps (A)	84-88	82/31	84-88	82/31
Starter Size	-	1	0/0	1	0/0
Thermal Protection	-	1.0	1.0	1.0	1.0
XP Motor Class - Group	-	Class B - Pilot Duty			
Shipping Weight	-	I-D	I-D	I-D	I-D
	Lbs	126	128	160	128
	Kg	57.2	57.2	86	57.2

**Voltage** - ROTRON motors are designed to handle a broad range of world voltages and power supply variations. Our dual voltage 3 phase motors are factory tested and certified to operate on both: 208-230/415-460 VAC-3 ph-60 Hz and 190-208/380-415 VAC-3 ph-50 Hz. Our dual voltage 1 phase motors are factory tested and certified to operate on both: 104-115/208-230 VAC-1 ph-60 Hz and 100-110/200-220 VAC-1 ph-50 Hz. All voltages above can handle a ±10% voltage fluctuation. Special wound motors can be ordered for voltages outside our certified range.

**Operating Temperatures** - Maximum operating temperature: Motor winding temperature (winding rise plus ambient) should not exceed 140°C for Class F rated motors or 120°C for Class B rated motors. Blower outlet air temperature should not exceed 140°C (air temperature rise plus inlet temperature). Performance curve maximum pressure and suction points are based on a 40°C inlet and ambient temperature. Consult factory for inlet or ambient temperatures above 40°C.

**Maximum Blower Amps** - Corresponds to the performance point at which the motor or blower temperature rise with a 40°C inlet and/or ambient temperature reaches the maximum operating temperature.

**XP Motor Class - Group** - See Explosive Atmosphere Classification Chart in Section I