

Serial#: EEI-1318

Date: 1/26/2017

Status: In stock

## Description:

- Falco 300 Electric Catalytic Oxidizer Including Vapor Control Valve, Flame Arrestor, 20' Exhaust

Stack

- Serial #: 10-300S-03FM

- Hours: 14,527 (as of 1/26/2017

•CAPACITY 100-350 scfm

•MAXIMUM 250 lb/day petroleum hydrocarbons @ 350 scfm

**INPUT LOADING** 

•VAPOR FALCO Vapor Control Valve (VCV)
CONTROL

•**DESTRUCTION** Up to 99.5%

EFFICIENCY

•CATALYST 330-620°C (626-1148°F)

TEMPERATURE RANGE

•CATALYST Packed bed 2.5 cubic feet. Platinum and Palladium on 1/8" ceramic beads standard.

•**HEAT** 304 Stainless steel spiral plate. 73% thermal efficiency @ 300 scfm (adjustable)

**EXCHANGER** 

•HEATER (Electric) 64.6 amps @ 240V (27 kW) Solid State Control

•CONSTRUCTION Stainless steel and aluminum

•WEIGHT 830 lb. with flame arrestor

•**DIMENSIONS** 73" high (excluding 5' stack) X 70" long X 29" wide Fits in the back of a pickup truck.

•**POWER** Heater 3Ø:

REQUIREMENTS

65 amp @ 240 VAC (27 kW) Controls: 120 VAC, 60 Hz

•APPROVALS Factory Mutual Approved for use in Class 1, Div 2, Group D, T2C Hazardous locations extending up to 41"

above the ground. South Coast Air Quality Management District (SCAQMD) Certified Equipment Permit.







**FALMOUTH PRODUCTS** P.O. BOX 541 FALMOUTH, MA 02541 PHONE 508-548-6686

CATALYTIC OXIDIZER

MODEL NUMBER FALCO 300

SERIAL NUMBER

10-3005-03

INSTALL PER INSTRUCTION MANUAL NUMBER SUITABLE FOR USE IN CLASSIFIED LOCATIONS AS DEFINED IN MANUAL.

CONTACTOR

ELECTRICAL RATINGS: CONTROLS 120 VOLTS, 3 AMP, 10, 60 HZ 230 VOLTS, 15 H.P., 30, 60 HZ

FM

**APPROVED** 

HEATER LOAD 240 VOLTS, 65 AMP, 30, 60 HZ

WARNING: THIS PRODUCT HAS MULTIPLE SOURCES OF ELECTRICAL SUPP



